Technology Investment Strategy Applied to the Mars Exploration Program

Presentation to the New Design Paradigms Workshop 2002, Pasadena, CA

C. Weisbin, B. Dolgin, J.H. Smith, C. Kohlhase, and G. Rodriguez

June 26, 2002

Wouldn't it be Nice if We Had This Table?

Annual Technology Investment (\$M)	Preferred Technologies	Missions Enabled	MEPAG Measurements <u>Enabled</u>	<u>Comments</u>	Technology Candidates (Different Pathway Mix; Sensitivity Analysis)
25	а	3	XX XX	Insufficient dollars to complete all technologies for mission X, resulting in measurements Y not being done.	XX
50	b c d e f	4 7 9	XX XX XX XX	Sensitivity of preferred tech #2 highly dependent on	XX XX XX XX
75	a d e f g	3 4 7 9	XX XX XX XX	Reduction in 75M/yr budget by 20% would result in	XX XX XX XX XX


Overview: Study Goal

- What is the best technology investment portfolio that enables a Mars exploration program that is resilient?
- Integrate three different sources of important information:
 - Program science return is evaluated based on a number of high priority MEPAG-defined measurements grouped into Pathways (McCleese/ Arvidson)
 - One measure of resiliency is the ability to be responsive to multiple possible futures (pathways) weighted according to Program policy
 - This analysis considered the 12 missions identified by the study leads under the direction of F. Jordan, plus 5 Scout classes identified by Steve Matousek.
 - The missions studied span the space of the various desired measurements
 - The missions identified the enabling capabilities/technologies
 - The technology metric, current state, performance forecast and funding requirements to achieve TRL-6 came from Samad Hayati.

crw: New Design Paradigm Workshop

3

Approach




Science Goals and Objectives

1	 Determine if Life Ever Arose on Mars ▶ Determine if Life Exits Today ▶ Assess the Extent of Prebiotic Chemical Evolution
2	 Determine the Evolution of the Surface and Interior of Mars (
3	 Determine the Climate History for Mars Characterize the Present Climate and Climate Processes Characterize the Ancient Climate and Climate Processes
4	 Prepare for Human Exploration Acquire Martian Environmenta Data Sets Conduct In-Situ Engineering Science Demonstrations Emplace Infrastructure for (Future) Missions

Figures of Merit

within Pathway





Number of Equivalent Priority 1

Figure of Merit Measurements for Mission within a Pathway

for a Mission =

Total Number of Equivalent Priority 1
Measurements within a Pathway




Figure of Merit for a Mission = Within Pathway mixture

Pathway Weight * Figure of Merit for a Mission within Pathway

Mission / Measurement Relationships

	Overall <u>FOM</u>		Number of Measurements with a Given Priority			
		<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>
Scouts	10	4	4	3	3	1
MSL	21	5	9	1	0	10
Volcanology Rover	4	3	0	0	4	1
Magnetometer Gravity Mission	5	2	1	2	0	0
SAR	.02	0	0	0	0	1
Atmospheric Mission Orbiter	12	4	5	1	8	3
Surface Science Orbiter	9	1	1	1	6	2
Polar Layer Deposit Rover	12	7	3	1	4	1
MSR	20	4	7	2	3	2
Wildcat	8	1	3	2	3	3
Sabertooth	8	2	4	4	2	5

* FOM \Rightarrow 60% In-Situ, 20% Global Cycle, 20% MSR

Priority "n" measurement is 3 times more valuable than priority "n+1"
All measurements performed constitute FOM=100. For measurements beyond MSL,
apply unity weight to categories of assigned (C), Primary (C1), and assigned secondary (C2)
measurements, apply 0.5 to auxiliary measurements (d).

For MSL, apply unity to assigned primary (C), apply 0.5 to TBD, apply 0.5 to partial measurements.

Technology Path Network




crw: New Design Paradigm Workshop 8

= technology not required

= data reference code

Data Sheet for Precision Landing





Attribute Definition: Semi-major axis of landing ellipse in kilometers

1. Estimate length of semi-major axis for this technology assuming task succeeds with probability 100%; (pick one)

2. Enter your estimate of actual probability of success that technology will be developed (0-100%).


85%

Estimate e

3. If the technology task fails, what is the best state-of-the-art likely to be achieved? (default—use current SOA)

100km

4. Estimate the budget profile in 3 year blocks (2002 M\$)



5. Enter total technology development cost for this technology (2002 dollars)

	estimate guess)	or	Range est (low to hig	
\$	М		-	\$M

Notes, Assumptions:

\$4M optical nav, \$4M G&C \$2M continuing to get TRL-6 in 05 (PDR) for MSL 09 launch; as soon as subsonic chute deployed, task is done. Could be continued if any post-MSL missions identify a need for tighter landing accuracy.

[Optional] This technology applies to following mission(s) (check all that apply if known, otherwise leave blank):

☑ VOL	□ SAR	図 MSR
□ ROV	□ IMA	🗷 WLD
□ RVL	□ SSC	⊠ SAB
□ MAG	⊠ POL	⊠ SCT ₁

We Do Have This Table!

Annual Technology Investment (\$M/yr)	<u>Preferred</u> <u>Technology</u>	Missions Enabled	<u>Ena</u>	Meas. bled Number	<u>Comments</u>	Sensitivity <u>Analysis)</u>
25	o On-orbit science	o MAG orbiter	1	7	15 out of 2047 portfolios meet	XX
	o Telecom network, navigation	o SAR orbiter	2	6	this budget constraint. Other	XX
Cost Profile	o Multimission survivability orb.	o Imag/Atmos	3	3	mission portfolios eliminated	
(2002 \$M):	•	orbiter	4	8	by larger number of required	
		o Surface Sci.	5	9	technologies, hence larger	
[13, 13, 13, 8.4, 8.4, 8.4, 0, 0, 0, 0, 0, 0]		orbiter	FOM	I = 14	investment costs that violate budget.	

We Do Have This Table!

Annual Technology Investment (\$M/yr)	Preferred Technology	Missions Enabled	Ena	G Meas. bled Number	<u>Comments</u>	Sensitivity Analysis)	
50a {Min Cost} Cost Profile (2002 \$M): [45.5, 45.5, 45.5,	o Precision landing o Impact attenuation o Hazard avoidance o Forward planetary protection o Sample characterization, surface o Sub-surface access, shallow o Mobility	o MSL o Scouts o POL	1 2 3 4 5	17 23 8 15 11	225 out of 2047 portfolios meet budget constraint. Other mission portfolios driven by larger number of required technologies, hence larger investment costs; options with higher technology value and	See 50b option for option to maximize number of missions.	
17.7, 17.7, 17.7, 16, 16, 16, 5, 5, 5]	o Sample handling, contam. o Telecom network, navigation o Multimission survivability: lander o Scouts		FOM = 30		smaller budgets possible, but pathways influence eliminates. This option maximizes technology, but minimum cost criterion only allows 3 missions.		
50b {Max missions} Cost Profile (2002 \$M): [46.5, 46.5, 46.5, 22.4, 22.4, 22.4	o Precision landing o Impact attenuation o Hazard avoidance o Forward planetary protection o Sample characterization, surface o Sub-surface access, shallow o <sub-surface 30m="" access,=""></sub-surface>	o MSL o Scouts o Volcanology o POL PLUS o MAG orbiter o WLD	1 2 3 4 5	19 25 10 16 15	Same as 50a except 3 additional missions enabled because not minimizing costÑ only has to be less than 50M/yr cap MAG allowed in because it does not require on-orbit	XX XX	
40.5, 40.5, 40.5, 22.4, 22.4, 20, 20, 20, 10, 10, 10] **Sub-surface access, 5um/ **Sub-surface access, DEEP/ **Mobility* **Sub-surface access, DEEP/ **Mobility* **Sub-surface access, 5um/ **Sub-sub-sub-sub-sub-sub-sub-sub-sub-sub-s		o SAB	FOM = 36		Science technology program and multimission survivability: orb low in cost.		

We Do Have This Table!

F	

Annual Technology Investment (\$M/yr)	Preferred Technology	Missions Enabled	<u>Ena</u>	Meas. bled Number	<u>Comments</u>	Sensitivity <u>Analysis</u>)
50c+ {MSR Lower Limit} Cost Profile (2002 \$M):	Precision landing Impact attenuation Hazard avoidance Forward planetary protection Sample characterization, surface Sub-surface access, shallow	o MSL o MSR o Volcanology o POL	1 2 3 4 5	18 27 8 16 12	2047 portfolios meet this budget constraint. Slack in budget permits larger number of required technologies across missions; This case minimizes cost which excludes some missions.	XX XX
[52.2, 52.2, 52.2, 19.4, 19.4, 14, 14, 14, 3, 3, 3]	o Mobility o Sample handling, contam. o Back planetary protection o Telecom network, navigation o Mars Orbit Rendezvous o Multimission survivability: lander		FOM	l = 41	excludes some missions.	
75b {Max Missions} Cost Profile (2002 \$M): [65.2, 65.2, 65.2, 32.8,	o Precision landing o Impact attenuation o Hazard avoidance o On-orbit science o Forward planetary protection o Sample characterization, surface o Sub-surface access, shallow o Sub-surface access, 30m o Sub-surface access, deep	o MSL o MSR o Volcanology o POL PLUS o MAG orbiter o SAR orbiter o Imag/Atmos	1 2 3 4 5	27 36 12 25 20	This case maximizes number of missions enables allowing higher costs. Basic message: problem is unconstrained by this budget for the input costs.	XX XX XX XX XX
32.8, 32.8, 20, 20, 20, 10, 10, 10]	o Mobility o Sample handling, contam. o Back planetary protection o Telecom network, navigation o Mars Orbit Rendezvous o Multimission survivability: lander o Multimission survivability: orb. o Scouts	orbiter o Surface Sci orbiter o WLD o SAB o Scouts	FOM	l = 61		

Conclusions

- We have developed and demonstrated a method for allocation of technology investment which maximizes science return in a budget-constrained environment
 - The method synergistically includes Mars goals, pathways, measurements, missions, capabilities, technologies, costs, etc.
 - The method builds on the Pathways work of McCleese/Arvidson, the mission studies of Jordan, and the technology R&D program of Hayati
 - Early results seem plausible and interesting!

Recommendations for Further Activity

- Review the data inputs carefully and perform sensitivity analyses where appropriate
- Enter data for five separate Scout mission classes (rovers, landers, orbiters, aerials, networks)
- Develop data for graceful degradation when specified metric ranges are not achieved.
- Complement existing study with more intense focus on risk assessment and answering specific decision-related issues.